### Product Range Information

fix4fire stee	el concret	e screw				
Product Code	Size mm	Head Type	Drill Diameter mm Hard Substrates	Drill Diameter mm Softer Substrates	Minimum Screw Embedment mm	Unit Qty
211-100-010	6x32	Pan	5.5	5	19	100
211-100-020	6 x 32	Oval	5.5	5	19	100
clip4fire ste	eel cable o	clip				- A
Product Code	Size mm		Cable Accomodated mm		Unit Qty	Carton Qty
075-165-100	T&E 2.5		T&E 1-2.5		100	4,800
075-165-110	T&E 6		T&E 4-6		100	4,800
steel mini ti	runking c	able clip				
Product Code	Dim Length	ensions mm Width Height	Fixing Hole mm	Trunking type		Unit Qty
076-010-100	19	15 22.5	6.3	T2		50
076-010-110	29	15 32.5	6.3	T3&T4		50
clamp4fire	steel cab	le clamp				
Product Code	Cable Accomodated mm		Drill Dia. mm	Minimum Enbedment mm		Unit Qty
076-010-120	Up to 15 x 1.5 Cables		5.5	19		50
076-010-130	Up to 30 x 1.5 Cables		5.5	19		25
steel cable	ties					
Product Code	Length mm	Width mm	Max. Bundle Diameter mm	Min. Tensile Strength KG		Unit Qty
080-185-010	200	4.6	50	45		100
080-185-015	300	4.6	76	45		100
080-185-020	360	4.6	102	45		100
steel wall p	lugs					
Product Code	Plug Length mm	Drill Size mm	Imperial Screw Gauge	Metric Screw mm	Unit Qty	Carton Qty
125-340-010	30	6	8-10	4-5	100	2,000
125-340-020	32	8	10-14	5-6	100	2,000
steel space	r bar sa <u>do</u>	dle				
Product Code		ensions mm Width Height	Colour	Conduit Size mm		Unit Qty
076-010-010	56	22 26	White	20		10
		23 31		25		10



f in У 🕨

### **OLYMPIC FIXING PRODUCTS LIMITED** Venture Court, Metcalf Drive,

Altham, Accrington, Lancashire, BB5 5WH Conlig, County Down, BT23 7SU T: +44 (0)1282 778923 F: +44 (0)1282 779119

E: accrington@olympicfixings.co.uk

**OLYMPIC FIXINGS IRELAND LIMITED** 

3 Greenway Industrial Estate,

- **T:** +44 (0)2891 453724
- F: +44 (0)2891 465893

E: bangor@olympicfixingsireland.com

## 18th Edition Compliant Solutions for Electricians & Contractors

Information on the Olympic Fixings range

www.olympicfixings.com

# **mpic fixings**

# 18th Edition COMPLIANT Solutions from Olympic Fixings



warringtonfire

warringtonfire

### fix4fire

### steel concrete screw

- Successfully tested to BS 5839-1 by Warrington Fire
- Under test subjected to fire with mechanical shock and water spray
- 120 minute testing at 930°C
- All steel screw for direct fastening without the need for plugs
- Ideal for fixing new metal consumer units

### clip4fire steel cable clip

- Successfully tested to BS 5839-1 by Warrington Fire
- Under test subjected to fire with mechanical shock and water spray
- 120 minute testing at 930°C
- All steel clip with 24mm manganese steel nail
- Two sizes to accommodate Twin & Earth cable up to 6mm

### mini trunking cable clip steel cable clip

- Successfully tested to BS 5839-1 by Warrington Fire
- Under test subjected to fire with mechanical shock and water spray
- 120 minute testing at 930°C
- Manufactured from galvanised steel
- For use in standard mini trunking

**Technical Data Sheets and Fire Test Results** are available on request for all Approved Products.







- - UV resistant and halogen free • Manufactured from 316 grade stainless steel
    - Available in 3 sizes up to 360mm length

• Ideal for applications where high strength,

corrosion and fire resistance are required

Resistant to fire, corrosion, solvents & chemicals

• Available in 2 sizes holding up to 30 1.5mm cables

Easy opening and closing mechanism

Manufactured from galvanised steel

### wall plug steel wall plugs

clamp4fire

steel cable clamp

cable ties

steel cable ties

• 18th Edition compliant

• 18th Edition compliant

- 18th Edition compliant
- All purpose heavy duty fixing
- Self centring internal guide for screw
- Manufactured from steel, zinc plated
- Ideal for most utility pipes, clips and meter boxes

### spacer bar saddle steel spacer bar

- 18th Edition compliant
- Resistant to fire, corrosion, solvents & chemicals
- Internal or external use
- Manufactured from galvanised steel and powder coated to RAL 9010 semi gloss white
- Ideal for refurbishments or new installations