
Olympic Fixings Acrylic Decorators Caulk

Revision: 23/04/2016

Page 1 of 3

Reference nr DOP: 230279

Unique identification code of the product type:

Olympic Fixings Acrylic Decorators Caulk

Intended use or uses of the construction product:

Sealant for facade for interior application.

Construction product in accordance with applicable harmonised specifications:

EN 15651-1:2012: Type F -INT

System or systems of assessment and verification of consistency of performance of the construction product, as set out in Annex V:

System 4: for essential characteristics**System 3: for reaction to fire**

Name and contact address of the manufacturer as required pursuant to Article 11(5):

**Olympic Fixing Products Limited, 1-4 Venture Court, Metcalf Drive,
Accrington, Lancashire, BB5 5WH, UK**

The notified body:

**WFR GENT, NB 1173 has carried out Determination of the Product Type under system 3 for
reaction to fire.**

Olympic Fixings Acrylic Decorators Caulk

Revision: 23/04/2016

Page 2 of 3

Declared Performance: EN 15651-1:2012

| Essential Characteristics | Performance | Harmonised Technical Specification |
|-----------------------------|-------------|------------------------------------|
| Reaction to fire | Class E | EN 15651-1:2012 |
| Release dangerous chemicals | NPD | |
| Water and air tightness | | |
| Resistance to flow | ≤ 3 mm | |
| Loss of volume | ≤ 45% | |
| Elongation at break | ≥ 25% | |
| Durability | Pass | |

Conditioning:

Method A

Test substrate:Aluminium
Mortar

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by



Paul Gordon

Managing Director

Accrington, BB5 5WH, 13/10/2021



NB 1173

**Olympic Fixing Products Ltd, 1-4 Venture Court,
Metcalf Drive, Accrington, BB5 5WH, UK**

14

Reference nr DOP: 230279

EN 15651-1: 2012

Sealant for facade for interior application.

Olympic Fixings Acrylic Decorators Caulk

EN 15651-1:2012: Type F -INT

Conditioning:

Method A

Substrate:

Aluminium

Mortar

| Essential Characteristics | Performance | Harmonised Technical Specification |
|-----------------------------|-------------|------------------------------------|
| Reaction to fire | Class E | EN 15651-1: 2012 |
| Release dangerous chemicals | NPD | |
| Water and air tightness | | |
| Resistance to flow | ≤ 3 mm | |
| Loss of volume | ≤ 45% | |
| Elongation at break | ≥ 25% | |
| Durability | Pass | |