



- 1. Olympic Fixings CSK Cross Chipboard screws, 4.0 & 5.0mm diameter manufactured using A2 (grade 304) stainless steel.
- 2. Batch numbers are included on box and outer carton labels to allow batch identification.
- 3. Olympic Fixings CSK Cross Stainless Steel Chipboard Screws are intended for use in certain timber structures.
- 4. Manufacturer: Olympic Fixing Products Ltd,

Units 1 - 4 Venture Court,

Metcalf Drive,

Altham, Accrington, Lancashire BB5 5WH Factory No. 1

5. Tested to EN14592:2008 + A1:2012 by:

Strojirensky zkusebni ustav, s.p. Engineering Test Institute, Public Enterprise Hudcova 424/56b, 621 00 Brno, Czech Republic, Notified Body No. 1015

Test Report Reference 30-20540-15 & 30-20541-15

6. Declared of performance in accordance with EN14592:2008 + A1:2012

Olympic Fixing Products Ltd

Units 1-3 Venture Court, Metcalf Drive Altham, Accrington Lancashire BB5 5WH

Tel: 01282 778923 (5 lines) Fax: 01282 779119

Sales Enquiries: accrington@olympicfixings.co.uk
General Enquiries: accrington@olympicfixings.co.uk
New Account Requests: tc@olympicfixings.co.uk

Olympic Fixings Ireland Ltd

Unit 3, Greenway Industrial Estate Conlig, Co. Down BT23 7SU

Tel: 02891 453724 (4 lines) Fax: 02891 465893

Sales Enquiries: sales@olympicfixings.co.uk

www.olympicfixings.com

www.orympichxings.com

Company Registration No: 02666419 VAT Registration No: GB 598063891

Registered Office:

Units 1-3 Venture Court, Metcalf Drive, Altham, Accrington, Lancashire BB5 5WH





Quality products from the fixing specialists

Essential characteristics		Performance				Harmonised technical specification
Geometry	d(mm)	M4.0		M5.0		EN14952:2008+A1:20 12
Material		Stainless steel grade A2/304				
Characteristic yield moment M _{y,k} (Nmm)		2.463		4.468		EN14592:2008+A1:20 12 Tab. ZA1 art.6.3.4.1- 6.3.4.2
Characteristic withdrawal parameter f _{ax, k} (N/mm²)		Across fibre 17.68	Along fibre 13.45	Across fibre 17.87	Along fibre 13.11	EN14592:2008+A1:20 12
Timber density Pk (kg/m³)		420		420		Tab. ZA1 art.6.3.4.3
Characteristic head pull- through parameter fhead,k(N/mm²)		25.72		23.35		EN14592:2008+A1:20 12
Timber density Pk (kg/m³)		450		450		Tab. ZA1 art.6.3.4.4
Characteristic tensile capacity f _{tens,k} (kN)		3.32		5.82		EN14592:2008+A1:20 12 Tab. ZA1 art.6.3.4.5
Characteristic torsional ratio		1.96		1.98		EN14592:2008+A1:20 12
Timber density Pk (kg/m³)		450		450		Tab. ZA1 art.6.3.4.6
Corrosion protection		Stainless steel grade A2/304 service class 3 to EN1995-1-1				EN14592:2008+A1:20 12 Tab. ZA1 art.6.3.5 manufacturers declaration

7. The performance of the product identified is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

For and behalf of Olympic Fixing Products limited

Paul Gordon
Managing Director

Olympic Fixing Products Ltd

Units 1-3 Venture Court, Metcalf Drive Altham, Accrington Lancashire BB5 5WH

Tel: 01282 778923 (5 lines) Fax: 01282 779119

Sales Enquiries: accrington@olympicfixings.co.uk General Enquiries: accrington@olympicfixings.co.uk New Account Requests: tc@olympicfixings.co.uk **Olympic Fixings Ireland Ltd**

Unit 3, Greenway Industrial Estate Conlig, Co. Down BT23 7SU

Tel: 02891 453724 (4 lines) Fax: 02891 465893

Sales Enquiries: sales@olympicfixings.co.uk

www.olympicfixings.com

Registered Office:
Units 1-3 Venture Court, Metcalf Drive, Altham,
598063891 Accrington, Lancashire BB5 5WH