



- 1. Olympic Fixings Metal Insulation Fixings, all sizes from 8 x 60 to 8 x 200mm.
- 2. Batch numbers are included on box and outer carton labels to allow batch identification.
- 3. Olympic Fixings Metal Insulation Fixings are intended for use in attaching insulation materials & plasterboard products dowel type fasteners.
- 4. Manufacturer: Olympic Fixing Products Ltd,

Units 1 - 4 Venture Court,

Metcalf Drive,

Altham, Accrington, Lancashire BB5 5WH Factory No. 1

5. Tested to EN14566:2008 + A1:2009 by:

Dedal Attestation & Certification, 8230 Nesebar, "Mladost" 50, parter. 8000 Burgas, "Macedonia" 54 str. 1574 Sofia, "Geo Milev 132 str., Office 20 Bulgaria. Notified Body No. 1922

Test Report Reference NTHP150526001 dated 26.05.15

Olympic Fixing Products Ltd

Units 1-3 Venture Court, Metcalf Drive Altham, Accrington Lancashire BB5 5WH

Tel: 01282 778923 (5 lines) Fax: 01282 779119

Sales Enquiries: accrington@olympicfixings.co.uk General Enquiries: accrington@olympicfixings.co.uk New Account Requests: tc@olympicfixings.co.uk Olympic Fixings Ireland Ltd

Unit 3, Greenway Industrial Estate Conlig, Co. Down BT23 7SU

Tel: 02891 453724 (4 lines) Fax: 02891 465893

Sales Enquiries: sales@olympicfixings.co.uk

Company Registration No: 02666419 VAT Registration No: GB 598063891

www.olympicfixings.com

www.orympichxings.com

Registered Office: Units 1-3 Venture Court, Metcalf Drive, Altham, Accrington, Lancashire BB5 5WH





- 6. System of assessment and verification of consistency of performance (AVCP) of the construction products as set out in Construction Products Regulation (EU) 305/2011 Annex V: **System 4**.
- 7. Declared performance

Essential characteristics	Harmonised technical specification	Requirement	Test result
Flexural strength (bending behaviour)	EN 14566 5.5	No fastener shall show signs of breakage or cracking	No breakage No cracking
Withdrawal force	EN 14566 5.4	The withdrawal force from wood shall be at least 200 N	Passed
Protective treatment	EN 14566 5.7	Fasteners protected with zinc shall have a minimum coating thickness of 5µm (35g/m²)	10μm
Head dimensions and tolerances	EN 14566 5.3.3.3	No more than five shall fail	Passed
Diameter of shank	EN 14566 5.3.3.1	No more than five shall fail	Passed
Length	EN 14566 5.3.3.2	No more than five shall fail	Passed

8. The performance of the product identified is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

For and behalf of Olympic Fixing Products limited

Paul Gordon
Managing Director

Olympic Fixing Products Ltd

Units 1-3 Venture Court, Metcalf Drive Altham, Accrington Lancashire BB5 5WH

Tel: 01282 778923 (5 lines) Fax: 01282 779119

Sales Enquiries: accrington@olympicfixings.co.uk General Enquiries: accrington@olympicfixings.co.uk New Account Requests: tc@olympicfixings.co.uk **Olympic Fixings Ireland Ltd**

Unit 3, Greenway Industrial Estate Conlig, Co. Down BT23 7SU

Tel: 02891 453724 (4 lines) Fax: 02891 465893

Sales Enquiries: sales@olympicfixings.co.uk

www.olympicfixings.com

Registered Office: Units 1-3 Venture Court, Metcalf Drive, Altham, Accrington, Lancashire BB5 5WH