

1. Olympic Fixings CSK Cross Ruspert coated decking screws, sizes from 4.5 x 40mm to 5.0 x 100mm.
2. Batch numbers are included on box and outer carton labels to allow batch identification.
3. Olympic Fixings CSK Cross Ruspert coated decking screws are intended for use in certain timber structures.

4. Manufacturer: Olympic Fixing Products Ltd,  
Units 1 - 4 Venture Court,  
Metcalf Drive,  
Altham,  
Accrington,  
Lancashire  
BB5 5WH  
Factory No. 1

5. Tested to EN14592:2008 + A1:2012 by:

Slovenian National Building and Civil Engineering Institute - ZAG,  
Ljubljana,  
Notified Body No. 1404

Test Report Reference P 1059/12-630-1 dated 28.05.13

**Olympic Fixing Products Ltd**

Units 1-3 Venture Court, Metcalf Drive  
Altham, Accrington  
Lancashire BB5 5WH

Tel: 01282 778923 (5 lines)  
Fax: 01282 779119

**Sales Enquiries:** [accrington@olympicfixings.co.uk](mailto:accrington@olympicfixings.co.uk)  
**General Enquiries:** [accrington@olympicfixings.co.uk](mailto:accrington@olympicfixings.co.uk)  
**New Account Requests:** [tc@olympicfixings.co.uk](mailto:tc@olympicfixings.co.uk)

Company Registration No: 02367267 VAT Registration No: GB 572277230

**Olympic Fixings Ireland Ltd**

Unit 3, Greenway Industrial Estate  
Conlig, Co. Down  
BT23 7SU

Tel: 02891 453724 (4 lines)  
Fax: 02891 465893

**Sales Enquiries:** [sales@olympicfixings.co.uk](mailto:sales@olympicfixings.co.uk)

**[www.olympicfixings.com](http://www.olympicfixings.com)**

Company Registration No: 02666419 VAT Registration No: GB 598063891

**Registered Office:**

Units 1-3 Venture Court, Metcalf Drive, Altham,  
Accrington, Lancashire BB5 5WH

### 6. Declared performance in accordance with EN14592:2008 + A1:2012

Essential characteristics		Performance		Harmonised technical specification
Geometry	d(mm)	M4.5	M5.0	EN14952:2008+A1:2012
Material		ASTM standard SAE 1022, AL KILLED(MQ) EN 10083-2		EN14592:2008+A1:2012 clause 6.3.2
Characteristic yield moment $M_{y,k}$ (Nm)		4.171	5.803	EN 409:2009
Characteristic withdrawal parameter $f_{ax,k}$ (N/mm <sup>2</sup> )		16.25	16.82	EN 1382:1999
Characteristic head pull-through parameter $f_{head,k}$ (N/mm <sup>2</sup> )		17.78	40.62	EN 1383:1999
Characteristic tensile capacity $f_{tens,k}$ (kN)		7.76	9.50	EN 1383:1999
Timber density $P_k$ (kg/m <sup>3</sup> )		398.0	406.1	
Characteristic torsional strength $f_{tor,k}$ (Nm)		4.65	5.88	EN ISO 10666:1999
Characteristic torsional resistance $R_{tor,k}$ (Nm)		1.34	1.17	EN 15737:2009
Characteristic torsional ratio		3.47	5.01	EN 14592:2008 Annex B
Corrosion protection		1000 hours minimum		ASTM B 117

### 7. The performance of the product identified is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

For and behalf of Olympic Fixing Products limited



**Paul Gordon**  
Managing Director

**Olympic Fixing Products Ltd**  
Units 1-3 Venture Court, Metcalf Drive  
Altham, Accrington  
Lancashire BB5 5WH

Tel: 01282 778923 (5 lines)  
Fax: 01282 779119

**Sales Enquiries:** [accrington@olympicfixings.co.uk](mailto:accrington@olympicfixings.co.uk)  
**General Enquiries:** [accrington@olympicfixings.co.uk](mailto:accrington@olympicfixings.co.uk)  
**New Account Requests:** [tc@olympicfixings.co.uk](mailto:tc@olympicfixings.co.uk)

**Olympic Fixings Ireland Ltd**  
Unit 3, Greenway Industrial Estate  
Conlig, Co. Down  
BT23 7SU

Tel: 02891 453724 (4 lines)  
Fax: 02891 465893

**Sales Enquiries:** [sales@olympicfixings.co.uk](mailto:sales@olympicfixings.co.uk)

**[www.olympicfixings.com](http://www.olympicfixings.com)**

Company Registration No: 02666419 VAT Registration No: GB 598063891

**Registered Office:**  
Units 1-3 Venture Court, Metcalf Drive, Altham,  
Accrington, Lancashire BB5 5WH