



Quality products from the fixing specialists

Declaration of
Performance



1. Olympic Fixings Express Anchors, all sizes from 6 x 30 to 8 x 180mm.
2. Batch numbers are included on box and outer carton labels to allow batch identification.
3. Olympic Fixings Express Anchors are intended for use in certain structural timber products – dowel type fasteners.

4. Manufacturer: Olympic Fixing Products Ltd,
Units 1 - 4 Venture Court,
Metcalf Drive,
Altham,
Accrington,
Lancashire
BB5 5WH
Factory No. 1

5. Tested to EN14592:2008 + A1:2012 by:

Strojirensky Zkusebni Ustav, S. P.
Engineering Test Institute Hudcora 424/56b,
621 00 Brno
Czech Republic.
Notified Body No. 1045

Test Report Reference 30-10584/1 dated 16.09.15

6. Declared performance in accordance with EN14592:2008 + A1:2012

Olympic Fixing Products Ltd

Units 1-3 Venture Court, Metcalf Drive
Altham, Accrington
Lancashire BB5 5WH

Tel: 01282 778923 (5 lines)
Fax: 01282 779119

Sales Enquiries: accrington@olympicfixings.co.uk
General Enquiries: accrington@olympicfixings.co.uk
New Account Requests: tc@olympicfixings.co.uk

Company Registration No: 02367267 VAT Registration No: GB 572277230

Olympic Fixings Ireland Ltd

Unit 3, Greenway Industrial Estate
Conlig, Co. Down
BT23 7SU

Tel: 02891 453724 (4 lines)
Fax: 02891 465893

Sales Enquiries: sales@olympicfixings.co.uk

www.olympicfixings.com

Company Registration No: 02666419 VAT Registration No: GB 598063891

Registered Office:

Units 1-3 Venture Court, Metcalf Drive, Altham,
Accrington, Lancashire BB5 5WH

Geometry

Diameter	Required size mm	Measured Values mm					Uncertainty U	Harmonised technical specification
		# 1	# 2	# 3	# 4	# 5		
6mm	D 6 ± 0.4	6.083	6.058	6.060	6.080	5.971	$\pm 0.02\text{mm}$	EN 14592:2008 + A1:2012 art. 6.4.3
	L 78.5 ± 1.0	78.987	79.045	79.089	79.066	79.071	$\pm 0.005\text{mm}$	
8mm	D 8.1 ± 0.4	8.044	8.043	8.010	8.024	8.002	$\pm 0.02\text{mm}$	
	L 68.5 ± 1.0	68.967	68.952	68.670	68.894	68.884	$\pm 0.005\text{mm}$	

Characteristic Yield Moment $M_{y,k}$

Diameter	Characteristic yield moment $M_{y,k}$ (N mm)	Measurement uncertainty U M_y	Harmonised technical specification
6mm	10084	$\pm 684\text{Nmm}$	EN 14592:2008 + A1:2012 art. 6.4.4.2
8mm	19308	$\pm 1143\text{Nmm}$	

Characteristic value calculation carried out according to art. 4 EN 14 358

Durability (Corrosion protection)

Plating specification – zinc plated Cr3+ min 5µm service class 1 or 2

7. The performance of the product identified is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

For and behalf of Olympic Fixing Products limited



Paul Gordon
Managing Director

Olympic Fixing Products Ltd
Units 1-3 Venture Court, Metcalf Drive
Altham, Accrington
Lancashire BB5 5WH

Tel: 01282 778923 (5 lines)
Fax: 01282 779119

Sales Enquiries: accrington@olympicfixings.co.uk
General Enquiries: accrington@olympicfixings.co.uk
New Account Requests: tc@olympicfixings.co.uk

Company Registration No: 02367267 VAT Registration No: GB 572277230

Olympic Fixings Ireland Ltd
Unit 3, Greenway Industrial Estate
Conlig, Co. Down
BT23 7SU

Tel: 02891 453724 (4 lines)
Fax: 02891 465893

Sales Enquiries: sales@olympicfixings.co.uk

www.olympicfixings.com

Company Registration No: 02666419 VAT Registration No: GB 598063891

Registered Office:
Units 1-3 Venture Court, Metcalf Drive, Altham,
Accrington, Lancashire BB5 5WH