

Technical Data Sheet

Olympic Concrete Frame Screws

Also known as Olympic Masonry Screws

Heavy Duty Self Tapping Screws

- Screws into a pre-drilled hole without the need for a wall plug, cutting its own thread •
- For fixing directly into masonry and concrete •
- Shallow countersunk head
- Torx T-30 recess .
- High/Low thread design •
- Zinc plated & yellow passivated for corrosion resistance •
- All metal, none flammable fixing

Typical Applications

Ideal for the fixing of window and door frames, wood or metal profiles, battens, brackets, timber beams, panels & signs

Olympic Fixing Products Ltd

Units 1-3 Venture Court, Metcalf Drive Altham, Accrington Lancashire BB5 5WH

Tel: +44 (0)1282 778923 (5 lines) Fax: +44 (0)1282 779119

Sales Enquiries: accrington@olympicfixings.co.uk General Enquiries: accrington@olympicfixings.co.uk New Account Requests: tc@olympicfixings.co.uk

Olympic Fixings Ireland Ltd

Unit 3, Greenway Industrial Estate Conlig, Co. Down BT23 7SU

Tel: +44 (0)2891 453724 (4 lines) Fax: +44 (0)2891 465893

Sales Enquiries: bangor@olympicfixingsireland.com

www.olympicfixings.com

Registered Office:

Company Registration No: 02367267 VAT Registration No: GB 572277230

Company Registration No: 02666419 VAT Registration No: GB 598063891

Units 1-3 Venture Court, Metcalf Drive, Altham, Accrington, Lancashire BB5 5WH

olympic fixings

Quality products from the fixing specialists

Range Information

hange mornation						
Product Code	Size mm	Drill Diameter mm	Haad Diamatar mm	Minimum Hole Depth mm	Maximum Ficture Thickness.mm	Unit Oty
074-100-001	7.5x42	6	10	45	5	100
074-100-002	7.5x52	6	10	45	10	100
074-100-003	7.5x62	6	10	45	20	100
074-100-005	7.5x72	6	10	45	30	100
074-100-007	7.5x82	6	10	45	40	100
074-100-010	7.5x92	6	10	45	55	100
074-100-012	7.5 x 102	6	10	45	60	100
074-100-015	7.5x112	6	10	45	70	100
074-100-017	7.5x122	6	10	45	80	100
074-100-020	7.5x132	6	10	45	90	100
074-100-025	7.5x152	6	10	45	110	100
074-100-027	7.5x182	6	10	45	140	100

Recommended Loading

- Will vary according to density of substrate
- In C20/25 concrete
 - For fixture depth below 80mm 100KG maximum loading (circa 1.0kN)
 - For fixture depth above 80mm 150KG maximum loading (circa 1.5kN) _

Olympic Fixing Products Ltd

Units 1-3 Venture Court, Metcalf Drive Altham, Accrington Lancashire BB5 5WH

Tel: +44 (0)1282 778923 (5 lines) Fax: +44 (0)1282 779119

Sales Enquiries: accrington@olympicfixings.co.uk General Enquiries: accrington@olympicfixings.co.uk New Account Requests: tc@olympicfixings.co.uk

Olympic Fixings Ireland Ltd

Unit 3, Greenway Industrial Estate Conlig, Co. Down BT23 7SU

Tel: +44 (0)2891 453724 (4 lines) Fax: +44 (0)2891 465893

Sales Enquiries: bangor@olympicfixingsireland.com

www.olympicfixings.com

Technical

Data Sheet

Registered Office: Units 1-3 Venture Court, Metcalf Drive, Altham, Accrington, Lancashire BB5 5WH

Company Registration No: 02367267 VAT Registration No: GB 572277230

Company Registration No: 02666419 VAT Registration No: GB 598063891