

## Hexagon Rod Hangers

### Product Information

The Rod Hanger Concrete Bolt is a self-tapping anchor manufactured from carbon steel and can be used in various kinds of base materials. The undercutting function provides a positive anchorage without expanded strength.

### Applications

- Masonry, solid or hollow concrete
- Brick or marble or stone
- Beams or fencing or handrail
- Structural anchorage
- Factory equipment installation
- Permanent and temporary installation

### Features

- Excellent performance
- Quick and safe to install
- Undercutting function
- Expansion with no resistance

#### Olympic Fixing Products Ltd

Units 1-3 Venture Court, Metcalf Drive  
Altham, Accrington  
Lancashire BB5 5WH

Tel: 01282 778923 (5 lines)  
Fax: 01282 779119

**Sales Enquiries:** [accrington@olympicfixings.co.uk](mailto:accrington@olympicfixings.co.uk)

**General Enquiries:** [accrington@olympicfixings.co.uk](mailto:accrington@olympicfixings.co.uk)

**New Account Requests:** [tc@olympicfixings.co.uk](mailto:tc@olympicfixings.co.uk)

Company Registration No: 02367267 VAT Registration No: GB 572277230

#### Olympic Fixings Ireland Ltd

Unit 3, Greenway Industrial Estate  
Conlig, Co. Down  
BT23 7SU

Tel: 02891 453724 (4 lines)  
Fax: 02891 465893

**Sales Enquiries:** [sales@olympicfixings.co.uk](mailto:sales@olympicfixings.co.uk)

**[www.olympicfixings.com](http://www.olympicfixings.com)**

Company Registration No: 02666419 VAT Registration No: GB 598063891

#### Registered Office:

Units 1-3 Venture Court, Metcalf Drive, Altham,  
Accrington, Lancashire BB5 5WH

### Product Range & Load

#### - Single Threads M8/M10

Size	Drill Dia.	Across Flat	Hole Depth	Overall Length	M8 Internal Thread Length	M10 Internal Thread Length	Embedment Depth	Tightening Torque	Recommended Tensile Resistance	Applied Load (Grade 8.8)
	mm	mm	mm	mm	mm	mm	mm	Nm	kN	kg
M8/M6 x 35	6	13	50	55	10	N/A	40	25	1.5	80
M10/M6 x 35	6	13	50	55	N/A	10	40	25	1.5	80

#### - \_ Double Threads M10+M8

Size	Drill Dia.	Across Flat	Hole Depth	Overall Length	M8 Internal Thread Length	M10 Internal Thread Length	Embedment Depth	Tightening Torque	Recommended Tensile Resistance	Applied Load (Grade 8.8)
	mm	mm	mm	mm	mm	mm	mm	Nm	kN	kg
M8/M6 x 35	6	13	50	55	10	N/A	40	25	1.5	80
M10/M6 x 35	6	13	50	55	N/A	10	40	25	1.5	80

#### Olympic Fixing Products Ltd

Units 1-3 Venture Court, Metcalf Drive  
Altham, Accrington  
Lancashire BB5 5WH

Tel: 01282 778923 (5 lines)  
Fax: 01282 779119

**Sales Enquiries:** [accrington@olympicfixings.co.uk](mailto:accrington@olympicfixings.co.uk)

**General Enquiries:** [accrington@olympicfixings.co.uk](mailto:accrington@olympicfixings.co.uk)

**New Account Requests:** [tc@olympicfixings.co.uk](mailto:tc@olympicfixings.co.uk)

Company Registration No: 02367267 VAT Registration No: GB 572277230

#### Olympic Fixings Ireland Ltd

Unit 3, Greenway Industrial Estate  
Conlig, Co. Down  
BT23 7SU

Tel: 02891 453724 (4 lines)  
Fax: 02891 465893

**Sales Enquiries:** [sales@olympicfixings.co.uk](mailto:sales@olympicfixings.co.uk)

**[www.olympicfixings.com](http://www.olympicfixings.com)**

Company Registration No: 02666419 VAT Registration No: GB 598063891

#### Registered Office:

Units 1-3 Venture Court, Metcalf Drive, Altham,  
Accrington, Lancashire BB5 5WH