


Technical Data Sheet	Title: Packing Fragile	
Effective Date: May 2019	Prepared By: J Barber	
Issue Number: 3	Authorised By: J Barber	

Product Description

Noisy polypropylene tape with a high performance acrylic adhesive that is undersurface printed ensuring a high quality image with complete protection from print deterioration.

Applications

Carton sealing

Features & Benefits

Secure packaging less concealed shortages

Technical Performance

Description	Units	Value	Test Method
Total thickness	mic	43	-
Film thickness	mic	28	-
Initial tack	#	20	PSTC - 6
Peel adhesion	N/25mm, 180°c	7.24	PSTC – 1
Holding power	hrs	>24	PSTC - 7
Elongation at break	Kg/25mm	MD 140 TD 60	ASTM D- 882
Tensile strength	Kg/25mm	MD 9 TD 19	ASTM D – 882

Declaration of Conformity Information

REACH SVHC Status – NO SHVC present according to candidates list of 15th Jan 2019

RoHS Compliance Status – Not Applicable

Storage Details

Shelf life recommended 12 months from date of despatch at the moderate temperature and humidity environment.

The information supplied is accurate to the best of Olympic Fixings knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. This document does not form part of any contract with a customer (02/05/13)