



Olympic PVC Insulation Tape



Polyvinyl Chloride Tape

- Manufactured to BS 3924, EN 60454
- Flame retardant and self extinguishing
- Gauge 0.13mm
- Suitable for repair, insulation, colour coding, cable bundling, panel building, loom harnessing etc.
- Available in ten colours
- Individually wrapped and shrink wrapped in sleeves

Range Information

Product Code	Colour	Sleeve Oty	Carton Qty
19mm x 20m			
093-251-005	Black	8	48
093-251-010	Red	8	48
093-251-015	Blue	8	48
093-251-033	Grey	8	48
093-251-034	Green	8	48
093-251-020	White	8	48
093-251-025	Yellow	8	48
093-251-030	Green/Yellow	v 8	48
093-251-032	Brown	8	48

Product Code	Colour	Sleeve Oty	Carton Qty
19mm x 33m			
093-252-005	Black	8	48
093-252-010	Red	8	48
093-252-015	Blue	8	48
093-252-033	Grey	8	48
093-252-034	Green	8	48
093-252-020	White	8	48
093-252-025	Yellow	8	48
093-252-027	Violet	8	48
093-252-030	Green/Yellov	v 8	48
093-252-032	Brown	8	48

Product Code	Colour	Sleeve Qty	Carton Qty
50mm x 33m	1		
093-253-005	Black	6	24
093-253-010	Grey	6	24
093-253-020	White	6	24
093-253-015	Yellow	6	24

Olympic Fixing Products Ltd

Units 1-3 Venture Court, Metcalf Drive Altham, Accrington Lancashire BB5 5WH

Tel: +44 (0)1282 778923 (5 lines) Fax: +44 (0)1282 779119

Sales Enquiries: accrington@olympicfixings.co.uk General Enquiries: accrington@olympicfixings.co.uk New Account Requests: tc@olympicfixings.co.uk

Olympic Fixings Ireland Ltd

Unit 3, Greenway Industrial Estate Conlig, Co. Down BT237SU

Tel: +44 (0)2891 453724 (4 lines) Fax: +44 (0)2891 465893

Sales Enquiries: bangor@olympicfixingsireland.com

www.olympicfixings.com

Registered Office: Units 1-3 Venture Court, Metcalf Drive, Altham, Accrington, Lancashire BB5 5WH





Product Specification

SORT: PVC ELECTRICAL TAPE		TYP:PVC ELECTRIC	
CONSTRUCTION	RELEASE	CARRIER:PVC FILM	Adhesive:Natural Rubber

Users should assure themselves that the performance of the product is sufficient for their intended application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes.

Item	Unit	Data	Test Standard
Total Thickness	μm	130±10	ASTM D-1000
Initial tack(Ball test)	Ball no	≥5	ASTM D-1000
180° peel adhesion(to stainless steel)	N/IN	≥3	ASTM D-1000
Tensile Strength	N/IN	≥43	ASTM D-1000
Elongation	%	150	ASTM D-1000

Characteristic: Good insulativity, flame resistant, Withstand voltage, temperature resistance and material soft. Easy to use

Repair, insulation, colour coding. Applications:

Color: Available in ten colous

Storage and transportation conditions:

- Tape should be stored in temperature 20 ℃-30 ℃, dry 50 %-70 % humidity area away from direct sunlight, air conditioner and other heat sources.
- Tape jumbos should be placed vertically with good package and avoid to be pressed against glue
- Tape should be used within 12 months from the date of production.

Remarks: Surface that the tape is applied to should be clean, dry and fee of grease, oil, moisture, dirt and other conditions.

Conforms to Rohs and Reach

Olympic Fixing Products Ltd

Units 1-3 Venture Court, Metcalf Drive Altham, Accrington Lancashire BB5 5WH

Tel: +44 (0)1282 778923 (5 lines) Fax: +44 (0)1282 779119

Sales Enquiries: accrington@olympicfixings.co.uk General Enquiries: accrington@olympicfixings.co.uk New Account Requests: tc@olympicfixings.co.uk

Olympic Fixings Ireland Ltd

Unit 3, Greenway Industrial Estate Conlig, Co. Down BT23 7SU

Tel: +44 (0)2891 453724 (4 lines) Fax: +44 (0)2891 465893

Sales Enquiries: bangor@olympicfixingsireland.com

www.olympicfixings.com

Company Registration No: 02666419 VAT Registration No: GB 598063891

Registered Office: Units 1-3 Venture Court, Metcalf Drive, Altham, Accrington, Lancashire BB5 5WH