



Tetra 4-Way Expansion Plug

Attributes


- Versatile plug, suitable for any base material (solid and hollow) and for use with a wide range of screws and other types of fastening.
- Expands in 4 directions.
- Two different geometries to optimise fastening to all base materials.
- High quality nylon. Made of top quality polyamide
 6, a very strong, flexible material that allows perfect expansion of the plug.
- Usage temperature: from -40°C to +80°C

Applications


Tetra 4-way expansion plugs guarantee uniform fastening to the base material thanks to the expansion of their four segments. They are perfect for safe, multi-purpose fastenings to all types of materials, whether these are solid materials like concrete, solid brick, stone, adobe brick, or hollow materials like hollow concrete, hollow brick and plasterboard. Their careful design allows uniform distribution over the base material when it expands



8 anti-spin areas provide better fastening to the base material & avoid plug rotation during installation



The collar prevents the plug from getting stuck in the base material



Interior ridges aid the positioning of the screw

Olympic Fixing Products Ltd

Units 1-4 Venture Court, Metcalf Drive Altham, Accrington Lancashire BB5 5WH

External markings

indicate the diameter

of the drill bit & screw

Tel: +44 (0)1282 778923 (5 lines) Fax: +44 (0)1282 779119

Sales Enquiries: accrington@olympicfixings.co.uk
General Enquiries: accrington@olympicfixings.co.uk
New Account Requests: tc@olympicfixings.co.uk

Olympic Fixings Ireland Ltd

Unit 3, Greenway Industrial Estate Conlig, Co. Down BT23 7SU

Tel: +44 (0)2891 453724 (4 lines) Fax: +44 (0)2891 465893

Sales Enquiries: bangor@olympicfixingsireland.com

www.olympicfixings.com

Company Registration No: 02666419 VAT Registration No: GB 598063891

Registered Office:

Units 1-4 Venture Court, Metcalf Drive, Altham, Accrington, Lancashire BB5 5WH





Quality products from the fixing specialists

Product Code	Plug Diameter	Plug Dimensions	ao: Drill	h _{ef} =h _{nom} : effective depth	h ₁ : minimum drill hole depth	Recommended screw	
050-085-045	Ø6	6x30	6	30	40	4mm - 5mm	
050-085-050	Ø8	8x40	8	40	50	4mm - 6mm	
050-085-055	Ø10	10x50	10	50	60	6mm-8mm	
050-085-060	Ø12	12x60	12	60	70	8mm - 10mm	



MAXIMUM RECOMMENDED LOAD Nrec KG												
Ø PLUG	Ø6		Ø8		Ø10		Ø12					
Ø SCREW	Ø4mm Screw	Ø5mm Screw	Ø4-5mm Screw	Ø6mm Screw	Ø6mm Screw	Ø8mm Screw	Ø8mm Screw	Ø10mm Screw				
C20/25 Concrete	32	61	56	170	161	256	150	394				
Solid Brick	25	48	70	104	94	160	62	104				
Hollow Brick	37	39	22	20	30	48	53	54				
12.5mm Drywall	13	8	15	6	-	-	-	-				
2 x 12.5mm Drywall	7	12	11	17	26	10	ı	-				
15mm Drywall	28	34	34	36	36	35	ı	-				
2 x 15mm Drywall	33	39	39	60	76	77	-	-				
AAC2 Aerated Concrete	4	5	7	9	4	9	13	17				
AAC6 Aerated Concrete	21	23	24	59	71	87	47	125				

Olympic Fixing Products Ltd

Units 1-4 Venture Court, Metcalf Drive Altham, Accrington Lancashire BB5 5WH

Tel: +44 (0)1282 778923 (5 lines) Fax: +44 (0)1282 779119

Sales Enquiries: accrington@olympicfixings.co.uk
General Enquiries: accrington@olympicfixings.co.uk
New Account Requests: tc@olympicfixings.co.uk

Olympic Fixings Ireland Ltd

Unit 3, Greenway Industrial Estate Conlig, Co. Down BT23 7SU

Tel: +44 (0)2891 453724 (4 lines) Fax: +44 (0)2891 465893

Sales Enquiries: bangor@olympicfixingsireland.com

www.olympicfixings.com

Registered Office: Units 1-4 Venture Court, Metcalf Drive, Altham, Accrington, Lancashire BB5 5WH