

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

EVO-STIK GRIPFILL ADHESIVE Supercedes Date: 17-Aug-2022 Revision date 09-Jun-2023 Revision Number 3.02

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product Name	EVO-STIK GRIPFILL ADHESIVE
Other means of identification	
Pure substance/mixture	Mixture
1.2. Relevant identified uses of	the substance or mixture and uses advised against
Recommended use	Adhesives
Uses advised against	None known
1.3. Details of the supplier of the	ne safety data sheet
<u>Company Name</u> Bostik SA 420 rue d'Estienne d'Orves 92700 Colombes FRANCE Tel: +33 (0)1 49 00 90 00	<u>Supplier</u> Bostik Industries Limited Newtown, Swords Co. Dublin Ireland Tel: +353 (1) 8624900 Fax: +353 (1) 8402186
E-mail address	SDS.box-EU@bostik.com
1.4. Emergency telephone num	iber
Ireland United Kingdom	NPIC - National Poison Information Centre Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week) Healthcare Professionals: +353 (01) 8092566 (24 hour service) Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)
Europe	112
SECTION 2: Hazards ider	ntification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Chronic aquatic toxicity	Category 3 - (H412)
Flammable liquids	Category 2 - (H225)

2.2. Label elements

Contains Xylenes (o-, m-, p- isomers), Acetone, Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, Hydrocarbons, C6, isoalkanes, <5% n-hexa

EVO-STIK GRIPFILL ADHESIVE Supercedes Date: 17-Aug-2022 Revision date 09-Jun-2023 Revision Number 3.02



Signal word Danger

Hazard statements

H315 - Causes skin irritation
H319 - Causes serious eye irritation
H412 - Harmful to aquatic life with long lasting effects
H225 - Highly flammable liquid and vapour

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P273 - Avoid release to the environment

P280 - Wear protective gloves and eye/face protection

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P403 + P235 - Store in a well-ventilated place. Keep cool

P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU	CAS No.	Classification	Specific	M-Factor	M-Factor	REACH
	Index No).		according to	concentration limit		(long-ter	registration
			Regulation (EC) No.	(SCL)		m)	number
			1272/2008 [CLP]				
Xylenes (o-, m-, p-	(601-022-00-	1330-20-7	STOT SE 3 (H335)	-	-	-	01-2119488216-
isomers)	9)		STOT RE 2 (H373)				32-XXXX
5 - <10 %	215-535-7		Asp. Tox. 1 (H304)				
			Skin Irrit. 2 (H315)				
			Eye Irrit. 2 (H319)				

EVO-STIK GRIPFILL ADHESIVE

Revision date 09-Jun-2023 Revision Number 3.02

Supercedes Date: 17-Aug-2022

Acetone 5 - <10 %	(606-001-00- 8) 200-662-2	67-64-1	Acute Tox. 4 (H312) Acute Tox. 4 (H332) Flam Liq. 3 (H226) Aquatic Chronic 3 (H412) Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336)	-	-	-	01-2119471330- 49-XXXX
Hydrocarbons, C7, n-alkanes, isoalkanes,		RR-100219-3	Flam. Liq. 2 (H225) STOT SE 3 (H336) Asp. Tox. 1 (H304)	-	-	-	01-2119475515 33-xxxx
cyclics 5 - <10 %			Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam. Liq. 2 (H225)				
Hydrocarbons, C6, isoalkanes, <5% n-hexane 1 - <5 %	931-254-9	RR-100242-2	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam Liq. 2 (H225) (EUH066)	-	-	-	01-2119484651 34-XXXX
Ethylbenzene 1 - <2.5 %	(601-023-00- 4) 202-849-4	100-41-4	STOT RE 2 (H373) Asp. Tox. 1 (H304) Acute Tox. 4 (H332) Flam Liq. 2 (H225) Aquatic Chronic 3 (H412)	-	-	-	01-2119489370 35-XXXX

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Xylenes (o-, m-, p- isomers)	(601-022-00-9) 215-535-7	1330-20-7	2500	1990	4.8	-	-
Acetone	(606-001-00-8) 200-662-2	67-64-1	5800	-	-	-	-
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	RR-100219-3	-	-	-	-	-
Hydrocarbons, C6, isoalkanes, <5% n-hexane	931-254-9	RR-100242-2	-	-	-	-	-
Ethylbenzene	(601-023-00-4) 202-849-4	100-41-4	3500	15400	4.99	17.6	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

EVO-STIK GRIPFILL ADHESIVE Supercedes Date: 17-Aug-2022

Revision date 09-Jun-2023 Revision Number 3.02

Chemical name	Notes
Xylenes (o-, m-, p- isomers) - 1330-20-7	С

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.
4.2. Most important symptoms and	effects, both acute and delayed
Symptoms	May cause redness and tearing of the eyes. Burning sensation.
4.3. Indication of any immediate m	edical attention and special treatment needed
Note to doctors	No information available.
SECTION 5: Firefighting mea	asures
5.1. Extinguishing media	
Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.
Unsuitable extinguishing media	No information available.
5.2. Special hazards arising from t	he substance or mixture
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Hazardous combustion products	Carbon oxides. Carbon monoxide. Carbon dioxide (CO2). Silicon dioxide.
5.3. Advice for firefighters	
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

EVO-STIK GRIPFILL ADHESIVE Supercedes Date: 17-Aug-2022

Revision date 09-Jun-2023 Revision Number 3.02

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.
6.2. Environmental precautions	
Environmental precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.
6.3. Methods and material for conta	ainment and cleaning up
Methods for containment	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.
6.4. Reference to other sections	
Reference to other sections	See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use personal protection equipment. Avoid breathing vapours or mists. Keep away from Advice on safe handling heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. **General hygiene considerations** Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing. 7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the

EVO-STIK GRIPFILL ADHESIVE Supercedes Date: 17-Aug-2022

particular national regulations. Store in accordance with local regulations.
Keep at temperatures between 5 and 25 °C.
The information required is contained in this Safety Data Sheet.
Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Kaolin	-	TWA: 2 mg/m ³	TWA: 2 mg/m ³
1332-58-7			STEL: 6 mg/m ³
Xylenes (o-, m-, p- isomers)	TWA: 50 ppm	TWA: 50 ppm	TWA: 50 ppm
1330-20-7	TWA: 221 mg/m ³	TWA: 221 mg/m ³	TWA: 220 mg/m ³
	STEL: 100 ppm	STEL: 100 ppm	STEL: 100 ppm
	STEL: 442 mg/m ³	STEL: 442 mg/m ³	STEL: 441 mg/m ³
	*	Sk*	Sk*
Acetone	TWA: 500 ppm	TWA: 500 ppm	TWA: 500 ppm
67-64-1	TWA: 1210 mg/m ³	TWA: 1210 mg/m ³	TWA: 1210 mg/m ³
		STEL: 1500 ppm	STEL: 1500 ppm
		STEL: 3630 mg/m ³	STEL: 3620 mg/m ³
Ethylbenzene	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm
100-41-4	TWA: 442 mg/m ³	TWA: 442 mg/m ³	TWA: 441 mg/m ³
	STEL: 200 ppm	STEL: 200 ppm	STEL: 125 ppm
	STEL: 884 mg/m ³	STEL: 884 mg/m ³	STEL: 552 mg/m ³
	*	Sk*	Sk*

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNE	Derived No Effect Level (DNEL)					
Xylenes (o-, m-, p- isomers) (1330-20-7)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
Long term Systemic health effects worker	Dermal	180 mg/kg bw/d				
Long term Systemic health effects worker	Inhalation	77 mg/m³				
Short term Local health effects Systemic health effects worker	Inhalation	289 mg/m³				

Acetone (67-64-1)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	186 mg/kg bw/d	
Short term	Inhalation	2420 mg/m ³	

EVO-STIK GRIPFILL ADHESIVE

Local health effects worker			
Long term	Inhalation	1210 mg/m³	
Systemic health effects		-	
worker			

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Long term Systemic health effects	Inhalation	2085 mg/m³		
worker Long term Systemic health effects	Dermal	300 mg/kg bw/d		

Derived No Effect Level (DNEL)				
Acetone (67-64-1)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Consumer Long term Systemic health effects	Inhalation	200 mg/m ³		
Consumer Long term Systemic health effects	Dermal	62 mg/kg bw/d		
Consumer Long term Systemic health effects	Oral	62 mg/kg bw/d		

Hydrocarbons, C7, n-alkanes	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Long term Systemic health effects	Inhalation	447 mg/m ³			
Consumer Long term Systemic health effects	Dermal	149 mg/kg bw/d			
Consumer Long term Systemic health effects	Oral	149 mg/kg bw/d			

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Acetone (67-64-1)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10.6 mg/l
Freshwater - intermittent	21 mg/l
Marine water	1.06 mg/l
Microorganisms in sewage treatment	100 mg/l
Freshwater sediment	30.4 mg/kg dry weight
Marine water	3.04 mg/kg dry weight
Soil	29.5 mg/kg dry weight

8.2. Exposure controls

EVO-STIK GRIPFILL ADHESIVE

Supercedes Date: 17-Aug-2022

Engineering controls	Ensure adequate ventilation, especially in confined areas.
Personal protective equipment Eye/face protection Hand protection	Tight sealing safety goggles. Face protection shield. Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Gloves should be replaced regularly and if there is any sign of damage to the glove material.
Skin and body protection	Antistatic footwear. Wear fire/flame resistant/retardant clothing. Suitable protective clothing.
Respiratory protection	In case of inadequate ventilation wear respiratory protection. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387.
Environmental surrestants a surface	Do not allow into any agues, on the ground or into any hady of water

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

9.1. Information on basic physical and chemical properties	
Physical state Liquid	
Appearance Liquid	
Colour No information available	
Odour Solvent.	
Odour threshold No information available	
Property Values Remarks • Method	
Melting point / freezing point No data available None known	
Initial boiling point and boiling = 60 °C	
range	
Flammability Not applicable for liquids .	
Flammability Limit in Air None known	
Upper flammability or explosive No data available	
limits	
Lower flammability or explosive No data available	
limits	
Flash point -10 °C	
Autoignition temperature No data available None known	
Decomposition temperature None known	
pH No data available Not applicable. Insoluble in wa	ter.
pH (as aqueous solution) No data available None known	
Kinematic viscosity 500 mm ² /s @ 40°C	
Dynamic viscosity No data available	
Water solubility No data available. None known	
Solubility(ies) No data available None known	
Partition coefficient No data available None known	
Vapour pressure No data available None known	
Relative density No data available None known	
Bulk Density No data available	
Density 1.18	
Relative vapour density No data available None known	
Particle characteristics	
Particle Size No information available	
Particle Size Distribution No information available	
9.2. Other information	
Solid content (%) No information available	
VOC content No data available	

9.2.1. Information with regards to physical hazard classes Not applicable

EVO-STIK GRIPFILL ADHESIVE

Supercedes Date: 17-Aug-2022

9.2.2. Other safety characteristics No information available

SECTION 10: Stability and re	eactivity			
10.1. Reactivity				
Reactivity	No information available.			
10.2. Chemical stability				
Stability	Stable under normal conditions.			
Explosion data				
Sensitivity to mechanical impact	None.			
Sensitivity to static discharge	Yes.			
10.3. Possibility of hazardous reac	tions_			
Possibility of hazardous reactions	None under normal processing.			
10.4. Conditions to avoid				
Conditions to avoid	Heat, flames and sparks.			
10.5. Incompatible materials				
Incompatible materials	Strong acids. Strong bases. Strong oxidising agents.			
10.6. Hazardous decomposition pr	oducts			
Hazardous decomposition products	None under normal use conditions. Stable under recommended storage conditions.			
SECTION 11: Toxicological i	nformation			
11.1. Information on hazard class	es as defined in Regulation (EC) No 1272/2008			
Information on likely routes of exp	osure			
Product Information				
Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.			
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.			
Skin contact	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).			
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.			
Symptoms related to the physical, chemical and toxicological characteristics				
Symptoms	Redness. May cause redness and tearing of the eyes.			
Acute toxicity				

EVO-STIK GRIPFILL ADHESIVE Supercedes Date: 17-Aug-2022

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS documentATEmix (oral)>5000 mg/kgATEmix (dermal)23,253.60 mg/kgATEmix (inhalation-gas)>20000 ppmATEmix (inhalation-dust/mist)47.90 mg/lATEmix (inhalation-vapour)128.50 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Xylenes (o-, m-, p- isomers)	=3500 mg/kg (Rattus)	 > 1700 mg/kg (Oryctolagus cuniculus) > 4350 mg/kg (Oryctolagus cuniculus) 	= 11 mg/L (ATE)
Acetone	=5800 mg/kg (Rattus) 3000 mg/Kg (mouse)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	LD50 >5840 mg/kg Rat	LD50 >2920 mg/kg (Rattus)	LC50 >23.3 mg/L (4h)(Rat, vapour) (OECD 403)
Hydrocarbons, C6, isoalkanes, <5% n-hexane	>16750 mg/Kg (Rattus)	>3350 mg/Kg (Oryctolagus cuniculus) OECD 402	259354 mg/m ³ (vapour) (rat OECD 403)
Ethylbenzene	=3500 mg/kg (Rattus)	= 15400 mg/kg (Oryctolagus cuniculus)	=17.6 mg/L (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Acetone (67-64-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	еуе			irritant
Acute Eye					
Irritation/Corrosion					

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Xylenes (o-, m-, p- isomers) (1330-20-7)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin	Mouse	Dermal	No sensitisation responses
Sensitisation: Local Lymph Node			were observed
Assay			

Acetone (67-64-1)

Method	Species	Exposure route	Results
	Guinea pig	Dermal	Not a skin sensitiser
Sensitisation			

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT - single exposure	Based on available data, the classification criteria are not met.
STOT - repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.
11.2. Information on other hazard	ds
11.2.1. Endocrine disrupting pro	perties
Endocrine disrupting properties	No information available.
11.2.2. Other information	
Other adverse effects	No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Harmful to aquatic life with long lasting effects.

		— • • • •			• • -
• .	Fish			M-Factor	M-Factor
plants		microorganisms			(long-term)
-	LC50 96 h 2.6	EC50 = 0.0084	EC50 48 h = 3.4		
	mg/L	mg/L 24 h	mg/L (Dappnia		
	(Oncorhynchus	U U			
			3 /		
	203)				
-	LC5096h 4.74	EC50 = 14500	EC50 48 h		
	- 6.33 mL/L	mg/L 15 min	10294 - 17704		
	(Oncorhynchus	-	mg/L (Daphnia		
	mykiss)		magna Static)		
ErL50 (72h) =	LL50 (96h)	-	EL50 (48h) =		
10-30 mg/L	>13.4 mg/L		3.0 mg/L		
(Pseudokirchner	(Oncorhynchus		(Daphnia		
iella subcapitata)	mykiss)		magna)		
. ,	OECD 203		σ,		
EL50 (72h) =	LL50 (96h) =	-	EL50 (48h)=		
13.6 mg/l	18.27 mg/l		31.9 mg/l		
(Pseudokirchner	(Oncorhynchus		(Daphnia		
iella subcapitata)	mykiss)		magna)		
EC50 72 h 2.6 -	LC50 96 h = 4.2	EC50 = 9.68	EC50: 1.8 -		
11.3 mg/L	mg/L	mg/L 30 min	2.4mg/L (48h,		
(Pseudokirchner	(Oncorhynchus	EC50 = 96 mg/L	Daphnia magna)		
iella subcapitata)		24 h 🛛			
. ,	semi-static)				
	10-30 mg/L (Pseudokirchner iella subcapitata) EL50 (72h) = 13.6 mg/l (Pseudokirchner iella subcapitata) EC50 72 h 2.6 - 11.3 mg/L (Pseudokirchner	plants - LC50 96 h 2.6 mg/L (Oncorhynchus mykiss) (OECD 203) - LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss) - LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss) ErL50 (72h) = 10-30 mg/L (Pseudokirchner iella subcapitata) LL50 (96h) >13.4 mg/L (Oncorhynchus mykiss) EL50 (72h) = 13.6 mg/l (Pseudokirchner iella subcapitata) LL50 (96h) = 18.27 mg/l (Oncorhynchus mykiss) EC50 72 h 2.6 - 11.3 mg/L (Pseudokirchner iella subcapitata) LC50 96 h = 4.2 mg/L (Oncorhynchus mykiss)	plantsmicroorganisms-LC50 96 h 2.6 mg/LEC50 = 0.0084 mg/L 24 h(Oncorhynchus mykiss) (OECD 203)mg/L 24 h-LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)EC50 = 14500 mg/L 15 min-LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)EC50 = 14500 mg/L 15 minErL50 (72h) =LL50 (96h) > >13.4 mg/L (Oncorhynchus mykiss)-0ECD 203OECD 203-EL50 (72h) =LL50 (96h) = > 13.4 mg/L (Oncorhynchus mykiss)-0ECD 203OECD 203-EL50 (72h) =LL50 (96h) = 1 18.27 mg/l (Oncorhynchus iella subcapitata) mykiss)-EC50 72 h 2.6 - 11.3 mg/L (Pseudokirchner (Oncorhynchus mg/LEC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	plantsmicroorganisms-LC50 96 h 2.6 mg/LEC50 = 0.0084 mg/L 24 hEC50 48 h = 3.4 mg/L (Dappnia magna)-LC50 96 h 2.6 mg/L (Dacorhynchus mykiss) (OECD 203)EC50 = 14500 mg/L 15 minEC50 48 h 10294 - 17704 mg/L (Daphnia mg/L (Daphnia mg/L 15 min-LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)EC50 = 14500 mg/L 15 minEC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)ErL50 (72h) =LL50 (96h) > >13.4 mg/L (Oncorhynchus iella subcapitata)-EL50 (48h) = 3.0 mg/L (Daphnia 	plantsmicroorganisms-LC50 96 h 2.6 mg/L (Oncorhynchus mykiss) (OECD 203)EC50 = 0.0084 mg/L 24 hEC50 48 h = 3.4 mg/L (Dappnia magna)-LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)EC50 = 14500 mg/L 15 minEC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)-LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)EC50 = 14500 mg/L 15 minEC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)ErL50 (72h) =LL50 (96h) > > 13.4 mg/L (Oncorhynchus mykiss)-EL50 (48h) = 3.0 mg/L (Daphnia magna)EL50 (72h) =LL50 (96h) 18.27 mg/l (Pseudokirchner iella subcapitata)-EL50 (48h) = 31.9 mg/l (Daphnia magna)EL50 (72h) =LL50 (96h) = 18.27 mg/l (Oncorhynchus mg/L iella subcapitata)-EL50 (48h) = 31.9 mg/l (Daphnia magna)EC50 72 h 2.6 -LC50 96 h = 4.2 mg/L (Oncorhynchus mg/L 30 min 24 hEC50 : 1.8 - 2.4mg/L (48h, Daphnia magna)

12.2. Persistence and degradability

Persistence and degradability No information available.

EVO-STIK GRIPFILL ADHESIVE

Xylenes (o-, m-, p- isomers) (1330-20-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	28 days	biodegradation	87.8 % Readily biodegradable
Biodegradability: Manometric			
Respirometry Test (TG 301 F)			

Acetone (67-64-1)

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready	28 days	biodegradation	91 % Readily biodegradable
Biodegradability: CO2 Evolution Test	-	-	
(TG 301 B)			

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	28 days	98%	Readily biodegradable
Biodegradability: Manometric			
Respirometry Test (TG 301 F)			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Xylenes (o-, m-, p- isomers)	3.15
Acetone	-0.24
Hydrocarbons, C6, isoalkanes, <5% n-hexane	3.6
Ethylbenzene	3.6

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment	
Xylenes (o-, m-, p- isomers)	The substance is not PBT / vPvB	
Acetone	The substance is not PBT / vPvB PBT assessment does	
	not apply	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	The substance is not PBT / vPvB	
Hydrocarbons, C6, isoalkanes, <5% n-hexane	The substance is not PBT / vPvB	
Ethylbenzene	The substance is not PBT / vPvB	

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

EVO-STIK GRIPFILL ADHESIVE Supercedes Date: 17-Aug-2022

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances 15 01 10*: Packaging containing residues of or contaminated by dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note:	The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.
Land transport (ADR/RID) 14.1 UN number or ID number 14.2 UN proper shipping name 14.3 Transport hazard class(es) Labels 14.4 Packing group Description 14.5 Environmental hazards 14.6 Special precautions for user Special Provisions Classification code Tunnel restriction code Limited quantity (LQ) ADR Hazard Id (Kemmler Number)	UN1133 Adhesives 3 3 II UN1133, Adhesives, 3, II, (D/E) Not applicable 640C F1 (D/E) 5 L 33
IMDG 14.1 UN number or ID number 14.2 UN proper shipping name 14.3 Transport hazard class(es) 14.4 Packing group Description 14.5 Marine pollutant 14.6 Special precautions for user Special Provisions Limited Quantity (LQ) EmS-No. 14.7 Maritime transport in bulk according to IMO instruments	UN1133 Adhesives 3 II UN1133, Adhesives, 3, II, (-10°C c.c.) NP None 5 L F-E, S-D Annex II of MARPOL and the IBC Code Not applicable
Air transport (ICAO-TI / IATA-DGR 14.1 UN number or ID number 14.2 UN proper shipping name 14.3 Transport hazard class(es) 14.4 Packing group Description 14.5 Environmental hazards 14.6 Special precautions for user Special Provisions Limited quantity (LQ) ERG Code	UN1133 Adhesives 3 II UN1133, Adhesives, 3, II Not applicable

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS P5b - FLAMMABLE LIQUIDS

P5c - FLAMMABLE LIQUIDS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

This product contains

Chemical name	Reporting of suspicious transactions, disappearances and thefts	Restricted
Acetone - 67-64-1	X	

National regulations

15.2. Chemical safety assessment

EVO-STIK GRIPFILL ADHESIVE

Supercedes Date: 17-Aug-2022

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

- H225 Highly flammable liquid and vapour
- H226 Flammable liquid and vapour
- H304 May be fatal if swallowed and enters airways
- H312 Harmful in contact with skin
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H332 Harmful if inhaled
- H335 May cause respiratory irritation
- H336 May cause drowsiness or dizziness
- H373 May cause damage to organs through prolonged or repeated exposure
- H411 Toxic to aquatic life with long lasting effects
- H412 Harmful to aquatic life with long lasting effects

Notes relating to the identification, classification and labelling of substances

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

- vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals
- STOT RE: Specific target organ toxicity Repeated exposure
- STOT SE: Specific target organ toxicity Single exposure
- EWC: European Waste Catalogue
- LOW: List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)
- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- IATA: International Air Transport Association
- ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air
- IMDG: International Maritime Dangerous Goods
- RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method

EVO-STIK GRIPFILL ADHESIVE

Supercedes Date: 17-Aug-2022

Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)European Chemicals Agency (ECHA) (ECHA_API)EPA (Environmental Protection Agency)Acute Exposure Guideline Level(s) (AEGL(s))International Uniform Chemical Information Database (IUCLID)National Institute of Technology and Evaluation (NITE)NIOSH (National Institute for Occupational Safety and Health)Organisation for Economic Co-operation and Development Environment, Health, and Safety PublicationsOrganisation for Economic Co-operation and Development High Production Volume Chemicals ProgrammeOrganisation for Economic Co-operation and Development Screening Information Data SetPrepared ByProduct Safety & Regulatory AffairsRevision date09-Jun-2023

Revision note SDS sections updated: 2

Training Advice Provide adequate information, instruction, and training for operator

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1272/2008 and Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet